

Lámparas halógenas de medio/alto voltaje, un casquillo


Áreas de aplicación

- Trabajos profesionales de cine y TV




Características del producto


- Funcionamiento en la tensión de red: 120 V | 230 V | 240 V
- Temperatura del color: 2.900 K | 3.000 K (con vida útil más larga)
- Temperatura del color: 3.200 K (para trabajos profesionales de cine y TV)
- Temperatura del color: 3.400 K (para una máxima eficacia lumínica)




Hoja de datos gama de productos



358722_Halogen Lamp 64662



341357_HALOGEN STUDIO LAMP 64670



488277_HALOGEN LAMP 93591, 93592

Hoja de datos gama de productos

Datos técnicos

Descripción del producto	Información de producto	Datos eléctricos	Datos Fotométricos	Dimensiones y peso		
	Referencia para pedido	Tensión nominal	Temperatura de color	Diámetro	Largo	Campo iluminado
64501 150 W 120 V	64501 150W 120V	120 V	3250 K	12.0 mm	55.0 mm	11,0*2,2 mm ²
64502 150 W 230 V	64502 150W GX6.	230 V	3200 K	18.0 mm	55.0 mm	13,0*1,9 mm ²
64502 150 W 240 V	64502 150W 240V	240 V	3200 K	18.0 mm	55.0 mm	13,0*1,9 mm ²
64504 150 W 230 V	64504 A1/248 15	230 V	3200 K	18.0 mm	62.0 mm	9,6*12,5 mm ²
64505 200 W 230 V ¹⁾	64505 200W GX6.	230 V	3200 K	18.5 mm	53.0 mm	9,6*12,5 mm ²
64505 200 W 230 V ¹⁾	64505 200W 240V	240 V	3200 K	18.5 mm	53.0 mm	9,5*12,5 mm ²
64512 300 W 120 V ¹⁾	64512 300W GX6.	120 V	3350 K	18.5 mm	53.0 mm	10,0*12,5 mm ²
64514 300 W 120 V ¹⁾	64514 300W GX6.	120 V	3200 K	18.5 mm	53.0 mm	10,0*12,5 mm ²
64515 300 W 230 V ¹⁾	64515 300W 230V	230 V	3300 K	18.5 mm	53.0 mm	9,8*12,5 mm ²
64515 300 W 240 V ¹⁾	64515 300W GX6.	240 V	3350 K	18.5 mm	53.0 mm	10,0*12,5 mm ²
64516 300 W 230 V ¹⁾	64516 300W GX6.	230 V	3150 K	18.5 mm	53.0 mm	9,8*12,5 mm ²
64516 300 W 240 V ¹⁾	64516 300W GX6.	240 V	3150 K	18.5 mm	53.0 mm	9,7*12,5 mm ²
64540 650 W 230 V	64540 BVM 650W	230 V	3400 K	24.0 mm	57.5 mm	14,0*15,0 mm ²
64540 650 W 240 V	64540 BVM 650W	240 V	3400 K	24.0 mm	57.5 mm	14,0*15,0 mm ²
64573 1000 W 120 V ²⁾	64573 1000W 115	115...120 V	3400 K	24.0 mm	57.5 mm	14,0*14,0 mm ²
64575 1000 W 230 V	64575 1000W 230	230 V	3400 K	24.0 mm	67.5 mm	14,0*14,0 mm ²
64575 1000 W 240 V	64575 1000W GX6	240 V	3400 K	24.0 mm	67.5 mm	14,0*14,0 mm ²
64748XS 1000W 240V	64748 XS 1000W	240 V	3200 K	22.2 mm	95.0 mm	
64748XS 1000W 230V	64748 XS 1000W	230 V	3200 K	22.2 mm	95.0 mm	
64662 300 W 230 V ³⁾	64662 300W GY9.	230 V	2900 K	15.0 mm	80.0 mm	9,0*11,0 mm ²
64672 500 W 230 V	64672 M40 500W	230 V	2900 K	22.0 mm	89.9 mm	12,0*11,0 mm ²

Hoja de datos gama de productos

Descripción del producto	Información de producto	Datos eléctricos	Datos Fotométricos	Dimensiones y peso		
	Referencia para pedido	Tensión nominal	Temperatura de color	Diámetro	Largo	Campo iluminado
64672 500 W 240 V	64672 M40 500W	240 V	2900 K	22.0 mm	89.9 mm	12,0*11,0 mm ²
64686 650 W 230 V	64686 DYZ 650W	230 V	3200 K	21.0 mm	64.0 mm	10,0*10,0 mm ^{2 3)}
64686 650 W 240 V	64686 DYZ 650W	240 V	3200 K	21.0 mm	64.0 mm	10,0*10,0 mm ^{2 3)}
93592 400 W 230 V ²⁾	93592 400W 230V	230 V	3200 K	20.0 mm	77.0 mm	10,7*12,2 mm ²
64662 300 W 240 V	64662 M38 300W	240 V	2900 K	17.5 mm	80.0 mm	9,0*11,0 mm ²
64540 650 W 230 V	64540 650W GX6.	230 V	3400 K	22.0 mm	57.5 mm	
64686 650 W 230 V	64686 650W GY9.	230 V	3200 K	21.0 mm	64.0 mm	
64540 650 W 240 V	64540 650W GX6.	240 V	3400 K	22.0 mm	57.5 mm	
64686 650 W 240 V	64686 650W 240V	240 V	3200 K	21.0 mm	64.0 mm	

Descripción del producto	Diámetro del filamento	Duración de vida	Datos adicionales del producto	Capacidades	
		Duración	Casquillo (denominación estándar)	Posición de quemado	Regulable
64501 150 W 120 V	2,2 mm	50 h	GX6.35	h90	
64502 150 W 230 V	1,9 mm	50 h	GX6.35	Universal	
64502 150 W 240 V		50 h	GX6.35	Universal	
64504 150 W 230 V		25 h	G6.35	s 90	
64505 200 W 230 V ¹⁾	12,5 mm	25 h	GX6.35	s 90	
64505 200 W 230 V ¹⁾	12,5 mm	25 h	GX6.35	s 90	
64512 300 W 120 V ¹⁾	12,5 mm	15 h	GX6.35	s 90	
64514 300 W 120 V ¹⁾	12,5 mm	75 h	GX6.35	Other	
64515 300 W 230 V ¹⁾	12,5 mm	15 h	GX6.35	s 90	
64515 300 W 240 V ¹⁾	12,5 mm	15 h	GX6.35	s 90	
64516 300 W 230 V ¹⁾	12,5 mm	75 h	GX6.35	s 90	
64516 300 W 240 V ¹⁾	12,5 mm	75 h	GX6.35	s 90	
64540 650 W 230 V	15,0 mm	15 h	GX6.35	Universal	Sí
64540 650 W 240 V	15,0 mm	15 h	GX6.35	Universal	
64573 1000 W 120 V ²⁾	14,0 mm	15 h	GX6.35	Other	
64575 1000 W 230 V	14,0 mm	15 h	GX6.35	s	
64575 1000 W 240 V	14,0 mm	15 h	GX6.35	s	
64748XS 1000W 240V			GY9.5	S180	
64748XS 1000W 230V			GY9.5	S180	

Hoja de datos gama de productos

Descripción del producto	Diámetro del filamento	Duración de vida	Datos adicionales del producto	Capacidades	
		Duración	Casquillo (denominación estándar)	Posición de quemado	Regulable
64662 300 W 230 V ³⁾	11,0 mm	2000 h	GY9.5	Universal	
64672 500 W 230 V	11,0 mm	2000 h	GY9.5	Universal	
64672 500 W 240 V	11,0 mm	2000 h	GY9.5	Universal	
64686 650 W 230 V	10,0 mm	50 h	GY9.5	Universal	
64686 650 W 240 V	10,0 mm	50 h	GY9.5	Universal	
93592 400 W 230 V ²⁾	12,2 mm	75 h	GY9.5	s 90	
64662 300 W 240 V	11,0 mm	2000 h	GY9.5	Universal	
64540 650 W 230 V			GX6.35	Other	
64686 650 W 230 V			GY9.5	Universal	
64540 650 W 240 V			GX6.35	Other	
64686 650 W 240 V			GY9.5	Other	

Descripción del producto	Categorías específicas del país		Datos logísticos	Environmental information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
	Código ANSI	LIF	EAN 10 of contained light source	Date of Declaration
64501 150 W 120 V	Other		4008321746030	15-05-2024
64502 150 W 230 V	Other		4052899080751	17-05-2024
64502 150 W 240 V	Other		4052899363236	15-05-2024
64504 150 W 230 V	Other	A1/249	4052899101654	06-03-2024
64505 200 W 230 V ¹⁾	Other		4008321746078	15-05-2024
64505 200 W 230 V ¹⁾	Other		4008321746092	25-04-2024
64512 300 W 120 V ¹⁾	Other		4008321746115	15-05-2024
64514 300 W 120 V ¹⁾	Other	CP/96	4008321746139	15-05-2024
64515 300 W 230 V ¹⁾	Other		4008321746153	15-05-2024
64515 300 W 240 V ¹⁾	Other		4008321746177	15-05-2024
64516 300 W 230 V ¹⁾	Other	CP/97	4008321746191	15-05-2024
64516 300 W 240 V ¹⁾	Other	CP/97	4008321746214	15-05-2024
64540 650 W 230 V	BVM		4052899158221	15-05-2024
64540 650 W 240 V	BVM		4052899158245	15-05-2024
64573 1000 W 120 V ²⁾	Other			05-03-2024
64575 1000 W 230 V	EGY		4052899274556	15-05-2024
64575 1000 W 240 V	EGY		4052899274570	15-05-2024
64748XS 1000W 240V			4052899545380	22-05-2024
64748XS 1000W 230V			4052899545366	22-05-2024
64662 300 W 230 V ³⁾	Other		4052899015449	22-05-2024
64672 500 W 230 V	Other		4008321098559	22-05-2024
64672 500 W 240 V	Other		4008321098535	22-05-2024
64686 650 W 230 V	Other		4052899158269	05-03-2024

Hoja de datos gama de productos

Descripción del producto	Categorías específicas del país		Datos logísticos	Environmental information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
	Código ANSI	LIF	EAN 10 of contained light source	Date of Declaration
64686 650 W 240 V	Other		4052899158283	05-03-2024
93592 400 W 230 V ²⁾	Other		4050300481531	05-03-2024
64662 300 W 240 V	Other	M/38	4052899144248	22-05-2024
64540 650 W 230 V	Other			06-03-2024
64686 650 W 230 V	Other			06-03-2024
64540 650 W 240 V	Other			06-03-2024
64686 650 W 240 V	Other			06-03-2024

Descripción del producto	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
64501 150 W 120 V	4050300279237 4008321746030	No declarable substances contained	In work
64502 150 W 230 V	4008321133335 4008321746054 4052899080751 4052899363250	No declarable substances contained	In work
64502 150 W 240 V	4052899080775 4052899363236	No declarable substances contained	In work
64504 150 W 230 V	4052899101654	No declarable substances contained	No declarable substances contained
64505 200 W 230 V ¹⁾	4008321098436 4008321173881 4008321746078	No declarable substances contained	No declarable substances contained
64505 200 W 230 V ¹⁾	4008321098610 4008321746092	No declarable substances contained	No declarable substances contained
64512 300 W 120 V ¹⁾	4008321098634 4008321746115	No declarable substances contained	No declarable substances contained
64514 300 W 120 V ¹⁾	4008321098672 4008321746139	No declarable substances contained	No declarable substances contained
64515 300 W 230 V ¹⁾	4008321098696 4008321746153	No declarable substances contained	No declarable substances contained
64515 300 W 240 V ¹⁾	4008321189110 4008321746177	No declarable substances contained	No declarable substances contained
64516 300 W 230 V ¹⁾	4008321098733 4008321746191	No declarable substances contained	No declarable substances contained
64516 300 W 240 V ¹⁾	4008321098757 4008321746214	No declarable substances contained	No declarable substances contained
64540 650 W 230 V	4052899158221	No declarable substances contained	No declarable substances contained
64540 650 W 240 V	4052899158245	No declarable substances contained	No declarable substances contained
64573 1000 W 120 V ²⁾	4008321098832		In work

Hoja de datos gama de productos

Descripción del producto	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
64575 1000 W 230 V	4008321098856 4052899274556	No declarable substances contained	No declarable substances contained
64575 1000 W 240 V	4008321087775 4008321098450 4052899274570	No declarable substances contained	No declarable substances contained
64748XS 1000W 240V	4052899545380	No declarable substances contained	No declarable substances contained
64748XS 1000W 230V	4052899545366	No declarable substances contained	No declarable substances contained
64662 300 W 230 V ³⁾	4008321097873 4052899015449	No declarable substances contained	No declarable substances contained
64672 500 W 230 V	4008321098559	No declarable substances contained	No declarable substances contained
64672 500 W 240 V	4008321098535	No declarable substances contained	No declarable substances contained
64686 650 W 230 V	4052899158269	No declarable substances contained	No declarable substances contained
64686 650 W 240 V	4052899158283	No declarable substances contained	No declarable substances contained
93592 400 W 230 V ²⁾	4050300481531	No declarable substances contained	No declarable substances contained
64662 300 W 240 V	4052899144248	No declarable substances contained	No declarable substances contained
64540 650 W 230 V	4008321098818		In work
64686 650 W 230 V	4008321098498 4008321133359		In work
64540 650 W 240 V	4008321098795		In work
64686 650 W 240 V	4008321098511		In work

¹⁾ Con tecnología de pinzamiento de cuarzo

²⁾ A petición

³⁾ Con filamento monopiano

Hoja de datos gama de productos

Consejos de aplicación

Para más información detallada sobre la aplicación y gráficos vea la hoja de datos del producto.

Referencias / links

Para más información acerca de la tecnología de pinzado, consulte el siguiente folleto:

“A whole lotta shakin’ goin’ on!” Nuevas lámparas halógenas con tecnología de pinzado de cuarzo. (122 W 100 DE 08/05)

Aviso

Sujeto a cambios sin aviso. Excepto errores y omisiones. Asegúrese de utilizar la emisión más reciente.