

XBO 4000 W/DHP LL OFR

XBO DHP for digital cinema projection | Lámpara xenón de arco corto




Áreas de aplicación

- Cinema projection

Características del producto

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range



Hoja de datos de producto

Datos técnicos

Datos eléctricos

Corriente nominal	128 A
Potencia nominal	4000.00 W
Margen del control de corriente	95...137 A
Tensión nominal	33.0 V

Dimensiones y peso

Diámetro	60.0 mm
Largo	345.0 mm
Long. con casq pero sin pitones/conexión	295,00 mm
Longitud del cable de entrada	130 mm
Long. del centro luminoso (LCL)	123,0 mm
Distancia entre electrodos en frío	6.3 mm
Peso del producto	645.00 g
Longitud del cable	130.0

Duración de vida

Duración	1500 h
Service Warranty Lifetime	1900 h

Datos adicionales del producto

Casquillo ánodo (denominación norma)	SFaX27-14x80
Casquillo cátodo (denominación norma)	SFc27-16/55

Capacidades

Enfriamiento	Refrigeración forzada
Posición de quemado	p15/s15 ¹⁾

¹⁾ Para la posición de quemado vertical: Ánodo (+) arriba

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-03-2024
Primary Article Identifier	4062172114080
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Hoja de datos de producto

Declaration No. in SCIP database	68536058-a0f0-4f39-8967-a173bfd19c5b
----------------------------------	--------------------------------------

Hoja de datos de producto

Instrucciones de seguridad

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Logistical Data

Código del producto	Descripción del producto	Unidad de embalaje (Piezas/unidad)	Dimensiones (largo x ancho x alto)	Volúmen	Peso bruto
4062172114080	XBO 4000 W/DHP LL OFR	Embalaje de envío 1	500 mm x 204 mm x 204 mm	20.81 dm ³	1440.00 g

El código del producto mencionado describe la unidad más pequeña de la cantidad que se puede pedir. Una unidad de envío puede contener uno o más productos individuales. Al cursar un pedido, introduzca la cantidad de la unidad de envío o su múltiple.

Aviso

Sujeto a cambios sin aviso. Excepto errores y omisiones. Asegúrese de utilizar la emisión más reciente.